

Restraint Lanyards



- 14mm Twisted Rope Restraint Lanyard - available in lengths 1m / 1.5m / 2m
- Minimum Breaking Strength 22kN
- Certified to EN354:2010



- 14mm Twisted Rope Work Positioning Lanyard - max. length 2m
- Minimum Breaking Strength 15kN
- Certified to EN358:2000



- 44mm Tubular Webbing Shock Absorbing Expandable Lanyard
- Relaxed Length - 1.4m, Expanded Length - 2m
- Conforms to EN355:2002



- 12mm Twin Rope Restraint Lanyard
- With scaffold hooks and karabiner
- Lengths 1.5m / 2m
- Conforms to EN354:2010



- 44mm tubular Webbing Twin Shock Absorbing Expandable Lanyard
- With scaffold hooks and karabiner
- Lengths 1.5 / 2m
- Conforms to EN355:2002



- Steel Screw Lock Karabiner
- Conforms to EN362:2004

Ø 17 mm Gate Opening ← 25 kN → Breaking Strength 170 gms Weight



- Steel Scaffold Hook
- Conforms to EN362:2004

Ø 55 mm Gate Opening ← 23 kN → Breaking Strength 475 gms Weight

For more information, contact your local depot, or visit our website www.lgsgroup.co.uk