

Webbing Slings

LGS supply a complete range of webbing slings, from 1t to 20t, in a range of lengths from 1m onwards. Webbing slings offer a wide and flat load bearing surface, with reinforced eyes at both ends. Each sling is colour coded in accordance with EN 1492-1. Each sling is individually marked for easy identification, and are supplied with certification.



Item	Colour coded according to EN 1492-1	Working Load Limit with 1 webbing sling					Working Load Limit with 2 webbing sling			
		Straight lift	Choked lift	β			Straight lift up to 45	Choked lift up to 45	Straight lift 45-60	Choked lift 45-60
				0-7	7-45	45-60				
		1.0	0.8	2.0	1.4	1.0	1.4	1.12	1.0	0.8
WSDP-201	WLL 1T	1.000	800	2.000	1.400	1.000	1.400	1.120	1.000	800
WSDP-202	WLL 2T	2.000	1.600	4.000	2.800	2.000	2.800	2.240	2.000	1.600
WSDP-203	WLL 3T	3.000	2.400	6.000	4.200	3.000	4.200	3.360	3.000	2.400
WSDP-204	WLL 4T	4.000	3.200	8.000	5.600	4.000	5.600	4.480	4.000	3.200
WSDP-205	WLL 5T	5.000	4.000	10.000	7.000	5.000	7.000	5.600	5.000	4.000
WSDP-206	WLL 6T	6.000	4.800	12.000	8.400	6.000	8.400	6.720	6.000	4.800
WSDP-208	WLL 8T	8.000	6.400	16.000	11.200	8.000	12.000	8.960	8.000	6.400
WSDP-210	WLL 10T	10.000	8.000	20.000	14.000	10.000	14.000	11.200	10.000	8.000
WSDP-212	WLL 12T	12.000	9.600	24.000	16.800	12.000	16.800	13.440	12.000	9.600

For more information, contact your local depot, or visit our website www.lgsgroup.co.uk